

## Declaration of Performance for the building product: **MARMOX MultiBoard**



In accordance with UK Construction Products Regulations: 2020

This UK declaration of the performance of Marmox MultiBoard manufactured by Marmox-Egypt Ltd covers all essential characteristics required by BS-EN13164 as specified by EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (*Amendment etc.*) (*EU Exit*) Regulations 2019) and SI no. 1359/2020 (the Construction Products (*Amendment etc.*) (*EU Exit*) Regulations 2020.)

1. Unique Identification code of the product type.	Marmox MultiBoard		
2. Type, batch or serial number or any other element allowing identification of the construction product.	<ul> <li>Dimensions; various, Thickness: 4, 6, 10, 12.5, 20, 30, 40, 50, 80, 100mm</li> <li>Sloping variant: 10 – 33mm</li> <li>Curved variant: 20mm</li> <li>Boards are labelled with batch code.</li> </ul>		
<b>3.</b> Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer.	<ul> <li>Internal and external wall and floor insulation offering thermal insulation, resistance to the passage of water and decoupling underneath tiling, render and plaster.</li> <li>Lightweight tile backer board.</li> <li>Insulation board beneath electric under-tile heating.</li> </ul>		
<b>4.</b> Name, registered trade name or registered trade mark and contact address of the manufacturer	<ul> <li>Marmox-Egypt Ltd, 319 El-Haram Street, Giza, EGYPT</li> <li>Tel: +202 338 60 172</li> <li>E-mail: info@marmoxegypt.com</li> </ul>		
<b>5.</b> Name and contact address of the authorised representative whose mandate covers the tasks specified.	<ul> <li>Marmox UK Ltd, 101 Hopewell Drive, Chatham, Kent ENGLAND ME5 7NP</li> <li>Tel: 01634 835290</li> <li>E-mail: sales@marmox.co.uk</li> </ul>		
<b>6.</b> System of Assessment and Verification of Constancy of Performance.	AVCP 3		
7. Designated Technical Specification	BS-EN13164: 2012 + A1:2015 Thermal insulation products for buildings - factory made extruded polystyrene foam products  A Factory Production Control system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of this standard.  UK Approved Bodies responsible for testing: BBA (0836), University of Salford (1145), BTTG (0338)		
8. In case of the DoP concerning a construction product for which a ETA has been issued	N/A		



## 9. Declared performance:

Essential characteristics according to BS-EN13164: 2012 + A1:2015.

Characteristic	Testing Notified Body	Performance assessed	Performance Level
Reaction to Fire (to BS-EN 13501-1: 2010)	BTTG, Leeds (0338)	Reaction to Fire according to BS EN 11925-2: 2020.	Class E
Thermal Conductivity, $\lambda_{\text{10/dry}}$	University of Salford (1145)	λ value (assessed on <u>20mm</u> <u>thick board</u> : 18mm XPS @ 0.034W/mK and 2mm slurry @ 0.130W/mK)	0.036W/m.K
Thermal Resistance, R <sub>D</sub> (to BS-EN13164 & EN12667)	University of Salford (1145)	Declared R value, ds	4mm Marmox board note 1 (2mm XPS) = 0.06m <sup>2</sup> K/W 6mm Marmox board note 1 (4mm XPS) = 0.12m <sup>2</sup> K/W 10mm Marmox board (8mm XPS) = 0.25m <sup>2</sup> K/W 12.5mm Marmox board (10.5mm XPS) = 0.33m <sup>2</sup> K/W 20mm Marmox board (18mm XPS) = 0.56m <sup>2</sup> K/W 30mm Marmox board (28mm XPS) = 0.56m <sup>2</sup> K/W 40mm Marmox board (38mm XPS) = 1.18m <sup>2</sup> K/W 50mm Marmox board (48mm XPS) = 1.50m <sup>2</sup> K/W 60mm Marmox board (58mm XPS) = 1.50m <sup>2</sup> K/W 60mm Marmox board (58mm XPS) = 1.50m <sup>2</sup> K/W Marmox Curved Board (20mm) Max = 18mm XPS = 0.56m <sup>2</sup> K/W Marmox Sloping Board (10-33mm) Min. = 8mm XPS = 0.25m <sup>2</sup> K/W
Compressive Strength (to BS-EN 826: 2013)	BB (0836)	At 10% deformation	CS(10/Y) 400
Compressive Creep (to BS-EN 1606: 1997)	BBA (0836)	Stress applied at 35% of declared level (assessed on 50mm thick board)	CC(2.5/1.5/10)161
Water Permeability (to BS-EN 12087: 2013)	BBA (0836)	Water Absorption (assessed on 30mm thick board)	WL(T) 3

**Note 1:** 4mm and 6mm Marmox boards are not covered by BS-EN13164 and therefore cannot be UKCA marked.

This DoP is issued under the responsibility of the manufacturer's UK representative, Marmox-UK Ltd and signed for and on behalf of the manufacturer by Mark Bowman, Technical Manager for Marmox UK + Ireland: 25<sup>th</sup> August 2021

Mun 2