

Specification: Tile backer board on a traditional floorboards

Product Ref: Marmox Multiboard / Marmox SoundBoard

Product Use: Intermediate substrate to ceramic and stone tiling on a floor comprising separate traditional floorboards.

Manufacturer: Marmox Ltd

Address: Marmox UK Ltd, Caxton House, 101 Hopewell Drive, Chatham, Kent ME5 7NP.
01634 835290; Email: sales@marmox.co.uk; <http://www.marmox.co.uk/>.

Description: Extruded polystyrene covered on both sides with fibreglass mesh encased in a c.0.75mm layer of polymer modified concrete which permanently bonds the mesh to the polystyrene.
(Soundboard has an additional 2mm layer of SBR rubber on one face)

Dimensions	Multiboard: Width = 600mm, Length = 1250mm, Thickness = 4/6/10/12.5/20/30/40/50/60mm Soundboard: Width = 600mm, Length = 1250mm, Thickness = 8/12mm
-------------------	--

Properties: Resistant to external environment and temperatures.
Low thermal conductivity (0.034W/mK) unaffected by moisture.
Does not expand or contract as temperature and humidity alters.
Absorbs lateral movement in the sub-floor to reduce the risk of cracking in the tiled surface.
Completely impermeable to water.
SoundBoard only: *Impact Sound Insulation through a ceramic tiled surface (ΔL_w) = 20dB*

Authorities: ISO9001 (*Bureau Veritas*), Energy Saving Trust Recommended for insulation.

CE+UK Marking: EN13164 – T1 – CS(10\Y)400 – CC(2/1/10)115 – WL(T)3

Fixing Method: Marmox Multiboard / SoundBoard is fixed to the floorboards with continuous layer of tile adhesive *only – mechanical fixings must not be used on either type of Marmox board.*
This method is only appropriate when the floorboards are flat and stable. If a flat and stable surface cannot be guaranteed, an intermediate layer of plywood is required.

- The floorboards **must not flex or exhibit any vertical movement**. Any movement must be eliminated before fixing the Marmox boards.
- Boards are configured in a brick-bond pattern when possible.
- Marmox boards are fixed to the floorboards on a continuous bed of flexible cement-based tile adhesive applied with a 8/6mm notched trowel. If the floor is particularly uneven, a 20mm trowel may be used.
- Lay and evenly push the Marmox board into position and check the flatness. *If using SoundBoard, lay the rubber side down to the floor.*
- Lay subsequent Marmox boards with a small gap of c.2-3mm between boards
- Apply a line of Marmox MSP-360 into the gaps between boards which seals the boards together making a waterproof barrier.
- A 5mm gap is left between the boards and the wall which is also filled with Marmox MSP-360.
- Reinforcing tape (scrim tape) is applied over the joints just prior to tiling except in extreme wet areas (*e.g. where there is likely to be standing water*) where Marmox self-adhesive Waterproof Tape should be used instead.

Specification: Tile backer board on a traditional floorboards

Notes

Short boards are much easier to fix to floor than long boards (0.6 x 2.4m) or big boards (1.2 x 2.4m) but those dimensions are also approved for this application (longer boards are not manufactured in thicknesses less than 10mm)

Limitations:

1. Compounds containing organic solvents (*including solvent-based tile sealers*) must not be used.
2. Temperatures in excess of 75°C are not appropriate.
3. Tiles no smaller than 5cm x 5cm should be used on the floor.